

Hi,

I've been reviewing the files for the Calfirm TCmodel run, and there seems to be a major problem.

There's two NRUNDATA files in the ".../drafteis" directory, "calfirm.in" dated 6-5-95 and "calfirm.in.2" dated 6-1-95. The latter seems to incorporate the latest decisions on the California Assured Storage Alternative: 50,000 AF max storage and the lower (current) minimum instream flows. However, the former (12,000 AF max storage and DFG suggested minimum instream flows) seems to have been used as input to the Calfirm TCmodel run. The only part of the former (6-5-95) file I believe should have been used is the "instream flow targets" for the reservoirs in California, since instream flows are still an objective in the alternative albeit without those minimums suggested by DFG (but this wasn't discussed when we were last formulating the Calfirm alternative).

Below is a comparison showing the differences between the two NRUNDATA files. Maybe I'm missing something here as I don't know much about how the runs were made. But I think you should take a look at this.

John Sarna jsarna@water.ca.gov

40 VALUES OF "KALT" WITH I3 SPACING

both:	0	2	2	0	1	0	1	0	1	1	0	0	1	0	1	0	0	0	1	0
6-5:	0	0	1	1	0	1	0	2	0	0	1	1	1	1	1	0	0	0	0	1
6-1:	0	0	1	1	0	1	0	3	0	0	1	1	1	1	1	0	0	0	0	1

^  
2 is mandatory  
3 is targeted

40 VALUES OF "KAL2" WITH I3 SPACING x

both:	0	0	1	0	0	0	2	1	0	0	0	0	0	1	0	0	1	1	0	0
6-5:	0	0	0	0	0	0	0	1	0	0	2	0	2	1	0	1	1	0	0	0
6-1:	0	0	0	1	0	0	0	1	0	0	2	0	2	0	0	0	1	0	0	0

20 VALUES OF "KAL3" WITH I3 SPACING


6-5:	0	0	1	0	1	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0
6-1:	2	0	1	0	1	0	1	1	0	0	0	0	0	0	0	0	0	0	0	0

CALIFORNIA RESERVOIR STORAGE LIMITS

6-5:	0	0	1.5	0	0	12.0	0	12.
6-1:	0	0	5.0	0	0	60.0	0	60.0

INSTREAM FLOW TARGETS

6-5:	75	75	75	75	75	75	75	75	75	75
	75	75	INS 1							
6-1:	50	50	50	50	50	50	70	70	70	70
	70	70	INS 1,2							



6-5:	15	15	15	15	10	10	30	30	30	30
	10	10	INS 2							
6-1:	3	3	3	3	3	3	3	3	3	3
	3	3	INS 2,2							

6-5:	15	15	15	15	10	10	30	30	30	30
	10	10	INS 3							
6-1:	5	5	5	5	5	5	5	5	5	5
	5	5	INS 3,2							

6-5:	10	10	10	10	10	10	10	10	10	10
	10	10	INS 4							
6-1:	2	2	2	2	2	2	2	2	2	2
	2	2	INS 4,2							

6-5:	40	40	40	40	40	40	40	40	40	40
	30	30	INS 5							
6-1:	30	30	30	30	30	30	30	30	30	30
	30	30	INS 5,2							

6-5:	100	100	100	100	100	100	200	200	200	200
	200	200	INS 6							
6-1:	0	0	0	0	0	0	0	0	0	0
	0	0	INS 6,2							

6-5:	100	100	100	100	100	100	100	100	100	100
	100	100	INS 7							
6-1:	0	0	0	0	0	0	0	0	0	0
	0	0	INS 7,2							

6-5:	250	250	250	250	250	250	250	250	250	250
	250	250	INS 8							
6-1:	0	0	0	0	0	0	0	0	0	0
	0	0	INS 8,2							

6-5:	30	30	30	30	30	30	40	40	40	40
	30	30	INS 9							
6-1:	0	0	0	0	0	0	0	0	0	0
	0	0	INS 9,2							

MINIMUM FLOW IN INFLOW TO PYRAMID LAKE

6-5:	240	240	240	240	240	240	240	320	480	415
	400	280								
6-1:	0	0	0	0	0	0	0	0	0	0
	0	0								